



AC ENAMEL PAINT

SOLVENT BASED ACRYLIC ENAMEL PAINT

DESCRIPTION

AC Enamel Paint is a specially formulated acrylic solvent based decorative and protective wall paint. It is recommended for masonry surfaces of exterior and interior applications.

FEATURES

- Excellent weathering resistance
- High gloss
- Alkaline resistance
- Good water and mild chemicals resistance
- Fast dry
- Easy maintenance

TECHNICAL PROPERTIES

Drying Time	: Approx. 1 hour
Dried Film Thickness	: Approx. 25 microns
Flash point	: 38°C
Thinner	: Xylene or Toluene
Coverage	: Approx. 10 - 12 sq meters per litre depending on substrate condition.

APPLICATION

- No priming is required.
- Surface must be sound and clean; free from dirt, dust, grease and other contaminants. If there is any doubt, wash the surface thoroughly with detergent water. If there is loose paint, scrap it off or use water jet to clean. Allowed to dry completely before application.
- Do not apply on substrate earlier coated with emulsion paint.
- Dilute with xylene if necessary.
- Apply by roller or brush.
- Minimum 1 coat. Apply 2 coats for better hiding and uniform finishing.
- Avoid contact with rain or water before the paint dry.



Casual dining area



Guard House at Condominium Entrance

PRECAUTION MEASURES

Flammable! Keep away from spark and naked flame. Contain sensitizing solvent. Wear proper PPE eg. chemical resistant glove, respirator during application. If contact with skin, wash with soap water immediately.

SHELF LIFE

2 years in unopened container.

PACKING

Available in 5 and 18 litre tin.

COLOUR



Light Grey



Medium Grey



Dark Grey



Beige

Also available in white colour.

Colour may be vary subject to printing.

Disclaimer: Specification are subject to change without notification.

122014

CLP since 1947
HQ/SINGAPORE : CLP INTERNATIONAL PTE LTD
CHIN LEONG CONSTRUCTION SYSTEMS PTE LTD
TEL : +65-6265 2788
FAX : +65-6265 1240
Email : chinleong@clp.com.sg

MALAYSIA: CLP CONSTRUCTION SYSTEMS SDN BHD
SELANGOR
TEL : +60-3-3176 5099
FAX : +60-3-3176 2797
Email : clp@clp.com.my

MALACCA
TEL : +60-6-263 1677
FAX : +60-6-263 1215

JOHOR
TEL : +60-7-252 5385
FAX : +60-7-252 5391

KEDAH
TEL : +60-4-489 3066
Fax : +60-4-489 1877

PERAK
TEL : +60-5-292 6986 / 6976
FAX : +60-5-292 6936

INDONESIA :
PT RANGALO CLP
TEL : +62-21-581 3951
FAX : +62-21-581 3950
Email : rangalo@cbn.net.id

PT-CLP INDONESIA
ZHONG SHAN
TEL : +62-21-2931 5121
FAX : +62-21-2931 5133 / 28
Email : info@clpindo.com

THAILAND:
CLPI (THAILAND) CO LTD
TEL : +66-2769 5633
FAX : +66-2769 5612
Email : clpi@ksc.th.com

VIETNAM :
CLPI VIETNAM CO LTD
TEL : +84-8-3526 1033
FAX : +84-8-3526 1032
Email : sales@clp.com.vn

TAIWAN :
SIHTACO CO LTD
TEL : +886-2-2791 8539
FAX : +886-2-8192 6248
Email : Alice.Lee@sihtaco.com.tw
Michael.Ku@sihtaco.com.tw

HONG KONG :
CHIN LEONG INTERNATIONAL CO LTD
LAMERTON ASIA HOLDING LTD
TEL : +852-2542 2206
FAX : +852-2544 9563
Email : chinleong@chinleong.com.hk

CHINA:
LAMERTON CHEMICAL (SHANGHAI) CO LTD
SHANGHAI
TEL : +86-21-5830 7559
FAX : +86-21-6840 7408

ZHONG SHAN SOUTH ASIA CHEMICAL LTD
ZHONG SHAN
TEL : +86-760-8554 4111
FAX : +86-760-8554 4113