

# CL – BOND G8

# CEMENTITIOUS TILE ADHESIVE (GREY)

# **DESCRIPTION**

**CL–BOND G8** is a grey coloured premixed dry set cementitious adhesive, specially formulated with excellent bonding strength for interior and / or exterior fixing of absorptive and non-absorptive marble / wall and floor tiles. Also available in Green Label version.

#### **FIXES**

- Marble / Granite
- Porcelain / Homogenous / Ceramic / Mosaics tiles
- Stones materials and others

# **CERTIFICATIONS**

- TUV PSB Singapore
- Singapore Green Building Council  $\sqrt{\sqrt{\sqrt{\frac{1}{2}}}}$  Excellent
- Sirim Malaysia

#### TECHNICAL INFORMATION

Classification : C2TE

Initial Tensile Adhesion Strength :  $\geq 2 \text{ N/mm}^2 \otimes 28 \text{ day}$ 

(BS EN 12004-2:2017)

Working Time : 20-30 min depending on

climatic conditions

Initial Set Time : 4-6 hrs Final Set Time : 6-10 hrs

# **MIXING**

Use clean and potable water for mixing. Mix in the proportion of 20 kg of CL-Bond G8 with 5.0-5.25 litre of water. Add adhesive to water and mix thoroughly until a slump-free mix is obtained. Let it stand for 5 minutes, then remix. After slaking period, do not add water or other ingredients. During use, remix occasionally.

Alternatively, CL-Bond G8 can be used in conjunction with CN-Flex 1000 latex admixture to enhance and increase flexural, bonding and shear strengths where critical application is required, especially when installing on the wall.

For wet areas as well as water submerged areas such as swimming pools, CL-Bond G8 can be used with CL-Flex 303 to enhance the water resistance requirement.

#### SPREADING THE MIX

Prior to spreading the mix, do not soak marble or tile backing surface. Dampen dry backing only to achieve cure.

Do not spread the mix to surface that contains frost. It should be floated with pressure over an area not greater than can be covered with marble / tile while the mix remained plastic.

Spread the mix on the surface using a notched trowel to a depth of 5-6mm at approximately 1-2 sq. meter at one time. Comb with the notched trowel to obtain continuous horizontal ribs of adhesive. Ensure that the adhesive is wet when tiles are laid.

# **INSTALLATING TILE**

Immediately press tile freshly combed adhesive. To obtain adequate contact between tile and adhesive bed, tap and beat the tile so that no void occur within the adhesive.

For rib back tile, trowel a layer of adhesive on the back of tile to obtain full contact prior to placing the tile on the adhesive bed.

Do not place tile on adhesive bed that had been set, remove and discard old adhesive. Tapping and wetting of the tile will not provide bonding of adhesive that had been set too long.

#### **GROUTING**

Do not grout until tile is firmly set and restrict all traffic and other works for a minimum of 24 hours on floor installation.

### **COVERAGE**

Approximately 3 kg per sq m on a 3 mm bed. Recommended thickness is 3-8mm depending on tile size.

## **SHELF LIFE**

12 months in unopened bag, stored in cool and dry place.

### **PACKING**

Available in 20kg bag.

042508

Disclaimer: Specification are subject to change without notification.

INDONESIA: PT RANGALO CLP TEL: +62-21-581 3951 FAX: +62-21-581 3950

Email: rangalo@cbn.net.id

Email: clp@clp.com.my

 MALAYSIA: CLP CONSTRUCTION SYSTEMS SDN BHD

 SELANGOR
 MALACCA

 TEL: +60-3-3176 5099
 TEL: +60-6-263 1677 / +60-6-225 0540

KEDAH

TEL: +60-4-489 3066 Fax: +60-4-489 1877

**JOHOR** 

TEL: +60-7-252 5385 FAX: +60-7-252 5391 TEL: +60-5-292 6986 / 6976 FAX: +60-5-292 6936 PT-CLP INDONESIA

TEL: +62-21-2931 5121 FAX: +62-21-2931 5133 / 28