

CL – BOND G8T / W3T

THICK BED ADHESIVE FOR MARBLE / GRANITE/ LARGE TILE

DESCRIPTION

CL-BOND G8T / W3T is a grey / white coloured premixed dry set cementitious adhesive with high strength aggregate, formulated specially for thick bed installation of marbles, granite and large tiles. For interior / exterior fixing of absorptive and non-absorptive marbles, granite and large tiles with thickness of 5 to 15mm.

FIXES

Can be used for Marbles, Granites, Terrazo, Homogeneous Tiles, Ceramic and others. CL-Bond W3T is recommended for the installation of light coloured stones to prevent "shadowing".

TECHNICAL INFORMATION

Classification : C2E

Initial Tensile Adhesion Strength : $\geq 1 \text{N/mm}^2 \otimes 28 \text{ day}$

(BS EN 12004-2:2017)

Working Time : 20 - 30 minutes depending

Initial Set Time : 3-6 hrs Final Set Time : 4-8 hrs

MIXING

Use clean and potable water for mixing. Mix in the proportion of 25kg of CL-Bond G8T / W3T with 4.5 litre of water. Add adhesive to water and mix thoroughly until a slump-free mix is obtained. Let it stand for 5 minutes, then remix. After slaking period, do not add water or other ingredients. During use, remix occasionally.

Alternatively, CL-Bond G8T / W3T can be used in conjunction with CN-Flex 1000 latex admixture to enhance and increase flexural, bonding and shear strengths where critical application is required, especially when installing on the wall.

For wet areas as well as water submerged areas such as swimming pools, CL-Bond G8T / W3T can be used with CL-Flex 303 to enhance the water resistance requirement.

SPREADING THE MIX

Prior to spreading the mix, do not soak marble or tile backing surface. Dampen dry backing only to achieve cure.

Do not spread the mix to surface that contains frost. It should be floated with pressure over an area not greater than can be covered with marble / tile while the mix remained plastic.

SELANGOR TEL: +60-3-3176 5099 FAX: +60-3-3176 2797

Email: clp@clp.com.my

Spread the mix on the surface using a notched trowel to a depth of 10 - 30mm at approximately 1 - 2 sq. meter at one time. Comb adhesive with the notched trowel to obtain continuous horizontal ribs of adhesive. Ensure that the adhesive is wet when tiles are laid.

INSTALLATING TILE

Immediately press tile freshly combed adhesive. To obtain adequate contact between tile and adhesive bed, tap and beat the tile so that no void occur within the adhesive.

For rib back tile, trowel a layer of adhesive on the back of tile to obtain full contact prior to placing the tile on the adhesive bed.

Do not place tile on adhesive bed that had been set, remove and discard old adhesive. Tapping and wetting of the tile will not provide bonding of adhesive that had been set too long.

GROUTING

Do not grout until tile is firmly set and restrict all traffic and other works for a minimum of 24 hours on floor installation.

COVERAGE

Approximately 7 kg per sq m on a 5 mm bed.

SHELF LIFE

12 months in unopened bag, stored in cool and dry place.

PACKING

Available in 25kg bag.

022513

Disclaimer: Specification are subject to change without notification.

PT RANGALO CLP TEL: +62-21-581 3951 FAX: +62-21-581 3950

Email: rangalo@cbn.net.id

INDONESIA

MALAYSIA: CLP CONSTRUCTION SYSTEMS SON BHD

MALACCA TEL: +60-6-263 1677 / +60-6-225 0540 KEDAH TEL: +60-4-489 3066 Fax: +60-4-489 1877

JOHOR TEL: +60-7-252 5385 FAX: +60-7-252 5391

FAX: +86-21-6840 7408

PERAK TEL: +60-5-292 6986 / 6976 FAX: +60-5-292 6936 PT-CLP INDONESIA TEL: +62-21-2931 5121 FAX: +62-21-2931 5133 / 28

Email: info@clpindo.com