



# CL – GLAZE

A NATURAL COATING FOR PROTECTING AND  
ENHANCING THE NATURAL BEAUTY OF SLATE /  
STONES

## DESCRIPTION

**CL-GLAZE** is an acrylic clear coating that acts as sealer to protect and enhance the natural beauty of slates, pavers, stones, bricks, terracotta tiles, quarry and other concrete products.

## FEATURES

- Beautifies substrates with a glossy wet look finish.
- Repels against water, cooking oil, beverages, dirt, dust and most household chemicals.
- Protects against fungal growth.
- Good weathering resistant
- Gives good abrasion against light foot traffic.
- Seals substrates to prevent chipping.
- Is easy to clean and maintain.

## TECHNICAL INFORMATION

Appearance	: Clear liquid
Density @ 28°C	: 0.92 g/ml
Viscosity @ 28°C	: ~ 57 KU
Drying Time @ 28°C	
Touch Dry	: 1 hour
Hard Dry	: 1.5 - 2 hours
Light Foot Traffic	: 24 hours

## SURFACE PREPARATION

The substrate must be sound, dry, and free from rising dampness whilst the surface to be coated must be dry, clean, sound and free of oil, grease, dirt, dust, efflorescence and other contaminants. When in doubt about the surface, wash it down with light detergent solution and flush with water. Allow it to dry completely prior to application.

For removal of hardened cement or other difficult residue, diluted CL-Ceramic Cleaner (1 part to 5 parts of water) should be applied. Leave for a few minutes until the residue becomes softened or dissolved, then scrub with soft-bristled broom and flush off with water. DO NOT use on substrates that are sensitive to acid.

For removal of grease or oil, apply with general-purpose thinner. Scrub with a long-handle brush while rinsing with thinner. Wipe off excess thinner with clean cloth and leave it to dry prior to application. DO NOT use on substrates that are artificially coloured to avoid discoloration.

## APPLICATION

DO NOT DILUTE CL-GLAZE. Apply by brush or roller. Two coats are generally recommended for better protection. Allow the first coat to dry before applying second coat, usually about 1 hour apart.

## COVERAGE

Approximately 12 – 15 sq meter per litre depending on substrate's porosity.

## SAFETY MEASURES

- Flammable! Keep away from heat, sparks and open flame.
- Avoid contact with skin and eyes, including inhalation.
- Prolonged contact may cause irritation. If the symptom persists, seek medical attention.

## SHELF LIFE

2 years in unopened container, store in cool and dry place.

## PACKING

Available in, 5 litre bottle, 20 litre pail and 200 litre drum.

122010

Disclaimer: Specification are subject to change without notification.

CLP since 1947  
HQ/SINGAPORE: CLP INTERNATIONAL PTE LTD  
CHIN LEONG CONSTRUCTION SYSTEMS PTE LTD  
TEL : +65-6265 2788  
FAX : +65-6265 1240  
Email : chinleong@clp.com.sg

MALAYSIA: CLP CONSTRUCTION SYSTEMS SDN BHD  
SELANGOR MALACCA  
TEL : +60-3-3176 5099 TEL : +60-6-263 1677  
FAX : +60-3-3176 2797 FAX : +60-6-263 1215  
Email : clp@clp.com.my

JOHOR  
TEL : +60-7-252 5385  
FAX : +60-7-252 5391

KEDAH  
TEL : +60-4-489 3086  
Fax : +60-4-489 1877

PERAK  
TEL : +60-5-292 6986 / 6976  
FAX : +60-5-292 6936

INDONESIA :  
PT RANGALO CLP  
TEL : +62-21-581 3951  
FAX : +62-21-581 3950  
Email : rangalo@cbn.net.id

PT-CLP INDONESIA  
TEL : +62-21-2931 5121  
FAX : +62-21-2931 5133 / 28  
Email : info@clpindo.com

THAILAND:  
CLPI (THAILAND) CO LTD  
TEL : +66-2769 5633  
FAX : +66-2769 5612  
Email : clp@ksc.th.com

VIETNAM :  
CLPI VIETNAM CO LTD  
TEL : +84-8-3526 1033  
FAX : +84-8-3526 1032  
Email : sales@clp.com.vn

TAIWAN :  
SIHTACO CO LTD  
TEL : +886-2-2791 8539  
FAX : +886-2-8192 6248  
Email : Alice.Lee@sihtaco.com.tw  
Michael.Ku@sihtaco.com.tw

HONG KONG :  
CHIN LEONG INTERNATIONAL CO LTD  
LAMERTON ASIA HOLDING LTD  
TEL : +852-2542 2206  
FAX : +852-2544 9563  
Email : chinleong@chinleong.com.hk

CHINA:  
LAMERTON CHEMICAL (SHANGHAI) CO LTD  
SHANGHAI  
TEL : +86-21-5830 7559  
FAX : +86-21-6840 7408

ZHONG SHAN SOUTH ASIA CHEMICAL LTD  
ZHONG SHAN  
TEL : +86-760-8554 4111  
FAX : +86-760-8554 4113