



CL – PRIMER P1

HIGH QUALITY CLEAR SEALER / PRIMER

DESCRIPTION

CL-PRIMER P1 is a specially formulated synthetic emulsion that acts as a sealer or primer to provide better adhesion for various water-based cementitious and non-cementitious coating systems onto various types of substrate.

FIXES

- Can be applied to rigid sound surfaces of various substrates such as sand / cement screed, concrete bases, granolithic and others.
- For use with water based products only.

FEATURES

- Excellent bonding strength
- Excellent alkaline resistant
- Applicable to wet substrates
- Non-flammable

TECHNICAL INFORMATION

Appearance	: Milky white liquid
Specific Gravity	: Approx. 1.0 @ 25°C
Viscosity	: 100 cps @ 25°C
Drying Time	: 1– 2 hours depending on climatic condition
Bonding Strength	: > 0.5 N/mm ² (1:3 mortar on concrete)

SURFACE PREPARATION

Surface to be coated must be sound, clean - free of dirt, dust, grease, oil, wax, curing compounds and other contaminants. For cracks, voids, chipped edges, uneven surfaces and holes, repair with CL-Rapid Repair. Fresh concrete must be cured for at least 14 days prior to application.

APPLICATION

Do not dilute CL-Primer P1. SHAKE WELL BEFORE USE. Apply by soft, bristle brush or roller. Allow it to dry prior to further application, usually about 1 to 2 hours depending on climatic condition. For highly absorbent surfaces, 2 coats are generally recommended. Allow the first coat to dry before applying second coat, usually about 1 to 2 hours. Allow the finish coat to dry before further application.

COVERAGE

0.15 – 0.2 kg per sq meter depending on substrate porosity.

TOOLS CLEANING

Use brush or roller. Wash with water immediately after use.

SHELF LIFE

2 years when stored in cool and dry place, sealed in unopened container.

PACKING

Available in 5 kg bottle and 20 kg pail.

122010

Disclaimer: Specification are subject to change without notification.

CLP since 1947
HQ/SINGAPORE : CLP INTERNATIONAL PTE LTD
CHIN LEONG CONSTRUCTION SYSTEMS PTE LTD
TEL : +65-6265 5633
FAX : +65-6265 1240
Email : chinleong@clp.com.sg

MALAYSIA: CLP CONSTRUCTION SYSTEMS SDN BHD
SELANGOR
TEL : +60-3-3176 5099
FAX : +60-3-3176 2797
Email : clp@clp.com.my
MALACCA
TEL : +60-6-263 1677
FAX : +60-6-263 1215

JOHOR
TEL : +60-7-252 5385
FAX : +60-7-252 5391

KEDAH
TEL : +60-4-489 3066
Fax : +60-4-489 1877

PERAK
TEL : +60-5-292 6986 / 6976
FAX : +60-5-292 6936

INDONESIA :
PT RANGALO CLP
TEL : +62-21-581 3951
FAX : +62-21-581 3950
Email : rangalo@cbn.net.id

PT-CLP INDONESIA
ZHONG SHAN
TEL : +62-21-2931 5121
FAX : +62-21-2931 5133 / 28
Email : info@clpindo.com

THAILAND:
CLPI (THAILAND) CO LTD
TEL : +66-2769 5633
FAX : +66-2769 5612
Email : clpi@ksc.th.com

VIETNAM :
CLPI VIETNAM CO LTD
TEL : +84-8-3526 1033
FAX : +84-8-3526 1032
Email : sales@clp.com.vn

TAIWAN :
SIHTACO CO LTD
TEL : +886-2-2791 8539
FAX : +886-2-8192 6248
Email : Alice.Lee@sihtaco.com.tw
Michael.Ku@sihtaco.com.tw

HONG KONG :
CHIN LEONG INTERNATIONAL CO LTD
LAMERTON ASIA HOLDING LTD
TEL : +852-2542 2206
FAX : +852-2544 9563
Email : chinleong@chinleong.com.hk

CHINA:
LAMERTON CHEMICAL (SHANGHAI) CO LTD
SHANGHAI
TEL : +86-21-5830 7559
FAX : +86-21-6840 7408

ZHONG SHAN SOUTH ASIA CHEMICAL LTD
ZHONG SHAN
TEL : +86-760-8554 4111
FAX : +86-760-8554 4113